Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

HIGHLIGHTS

- Quickly & Efficiently Removes
 Concrete
- Can be Left on Equipment Overnight
- No Harsh Acids--Muriatic,
 Sulfuric, Phosphoric
- Non-Hazardous, Non-Toxic,
 Non-Flammable, Non-Corrosive
- Completely Biodegradable
- Active Ingredient is in "Face Peel" Cosmetics

TYPICAL PROPERTIES

Vapor Pressure: Vapor is water

Volatility: N/A

Solubility: Yes

Specific Gravity: 1.0625

Vapor Density: Vapor is water

● pH: **1.5**

Evaporation Rate: N/A

Physical Description:
 Clear liquid with acidic
 odor

SAFETY CAUTIONS

- Store out of reach of children.
- Store in closed, labeled containers.
- Refer to MSDS for additional safety information.



HMIS RATINGS

Flammability

Health

1

0

Reactivity

Personal Protection





KWIK SAND XT

Liquid

DESCRIPTION:

KWIK SAND XT is formulated specifically for the concrete industry to remove hardened concrete from trucks, equipment, forms, hoppers, pumps, tools, etc. KWIK SAND XT works without harsh acids like Sulfuric, Hydrofluoric, Muriatic and Phosphoric. It is so safe that it is classified as Non-Hazardous by the DOT. It has been formulated to remove large amounts of concrete build up

quickly. KWIK SAND XT will remove 1/8 to 1/4 of an inch of concrete at a time.

DIRECTIONS:

For best results, KWIK SAND XT should be brushed or sprayed on surface. Let the formulation remain on the surface at least 15 minutes. The dry hard concrete will be chemically changed to sand-like particles that may be brushed clean. KWIK SAND XT can be applied and left on overnight reducing costly overtime and labor.

The amount of application and time left on the surface will depend on the thickness of the concrete. May be diluted up to 4:1 with water.

manufactured by:

www.arrowmagnolia.com

ARROW-MAGNOLIA INTERNATIONAL, INC. 2646 Rodney Lane Dallas, Texas 75229 Toll Free: 800.527.2101 Fax: 972.484.2896