

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

HIGHLIGHTS

- Gear and Cable Lubricant
- Dual Spray Valve
- Becomes Tacky Quickly
- 16 Ounce Can

TYPICAL PROPERTIES

- Vapor Pressure: **N/E**
- Volatility: **N/A**
- Solubility: **Insoluble**
- Specific Gravity: **0.86**
- Vapor Density: **N/E**
- pH: **N/A**
- Evaporation Rate: **N/E**
- Physical Description:
Dark coarse spray with solvent odor

SAFETY CAUTIONS

- Keep out of reach of children.
- For industrial and institutional use only.
- Do not store at temperatures above 120 °F.
- Store in a cool, dry area away from heat or open flame.
- Refer to MSDS for additional safety information.

HMIS RATINGS



MOLY MITE

Aerosol

DESCRIPTION:

MOLY MITE is a super tough, adhesive type lubricant which penetrates deep into gears and cables and other mechanisms. It thickens quickly to provide a Molybdenum Disulfide shield which maintains a cushion of lubricant between gear teeth and other friction-producing surfaces. Absorbs high shock loads, extreme pressure and prevents chipping and scuffing. Forms a protective water-resistant coating to prevent corrosion in outdoor and even underwater applications. This product can be used on passenger and freight elevators, drag lines, mining equipment, cranes, construction equipment, winches, offshore drilling rigs and marine equipment.

DIRECTIONS:

SHAKE WELL. Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application.

DUAL SPRAY VALVE DIRECTIONS: Press valve down for fan spray to apply a uniform film. Tilt valve forward for jet stream application in hard to reach areas. Jet stream sprays approximately 8 feet.

distributed by:

ARROW MAGNOLIA INTERNATIONAL, INC.
2646 Rodney Lane
Dallas, Texas 75229
Toll Free: 800.527.2101
Fax: 972.484.2896
www.arrowmagnolia.com