

liquid concrete removers

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

HIGHLIGHTS

- Rust and Concrete Remover
- Rapid Action
- Highly Concentrated
- Minimal Fuming
- Non-Hazardous to Handle
- Will Not Damage Paint or Similar Surfaces

TYPICAL PROPERTIES

- Vapor Pressure: **45**
- Volatility: **72**
- Solubility: **Yes**
- Specific Gravity: **1.141**
- Vapor Density: **N/A**
- pH: **0.5**
- Evaporation Rate:
Slower than ether
- Physical Description:
Clear bluish/purple liquid with acidic odor

SAFETY CAUTIONS

- Store out of reach of children.
- Store in closed containers in acid resistant plastic containers.
- Store in closed, labeled containers.
- Do not store near strong alkaline or reactive.
- Refer to MSDS for additional safety information.

HMIS RATINGS



RUST CON-X

DESCRIPTION:

RUST CON-X is specially formulated to safely remove dried concrete and rust from hard metal surfaces. Unlike Muriatic Acid, it contains special buffers that allow for easy handling while still being highly effective.

RUST CON-X has a wide variety of applications, from the concrete industry - forms, rings and other equipment - to anyone concerned with removing rust from metal surfaces. This product, when used as directed, will absolutely remove concrete and rust without harming a painted surface, plastic or hard metal.

DIRECTIONS:

RUST CON-X can be diluted up to 10:1 with water depending on the thickness and age of the rust or concrete.

RUST CON-X should be applied by proper spray equipment or applied by brush and bucket method. On difficult areas, brush agitation is always recommended. RUST CON-X may also be used in poly or fiberglass dip operation with a two hour limited time span.

When equipment is completely free of rust and concrete, rinse well with a diluted solution of BULLDOZER. Equipment must be thoroughly rinsed.

When completely dry, apply MIRROR KOTE or TREX II for a beautiful protective finish. MIRROR KOTE for painted surfaces; TREX II for unpainted steel surfaces.

Do not use on soft metals such as aluminum and magnesium.

manufactured by:

ARROW - MAGNOLIA INTERNATIONAL, Inc.
2646 Rodney Lane
Dallas, Texas 75229
Toll Free: 800.527.2101
Fax: 972.484.2896
www.arrowmagnolia.com